

STONEBLAZER FLOOR WET LOOK- MATTE/GLOSS

WEATHERPROOFING AND STAIN RESISTANT WITH WEL LOOK



Product Description:

STONEBLAZER FLOOR- WET/GLOSS is solventless third generation composition act as a penetrating sealer with no visual layer. This intensifies the natural colour of the substrate & maintaining their natural feel. This is specially developed two in one solution for lasting beauty. Colours come out brighter and deeper with gloss or matte effects as well it protects the surface from water & oil-based stains. This UV stable unique composition is ideal for protection of new or old absorbent & dense mineral based interior & exterior substrates. It provides, excellent water repellency to reduce cracking, spalling, chemical degradation, biological growth, efflorescence, and dirt pickup. There by lengthening substrate life and reducing maintenance costs.

Benefits:

- ⊙ Ready to use.
- ⊙ Can be applied by brush, roller, cloth or sponge.
- ⊙ Very thin liquid - deep penetration - No surface sealing.
- ⊙ Substrate stays breathable and natural.
- ⊙ Excellent colour enhancement.
- ⊙ Wet look (gloss) or matte effect is possible.
- ⊙ Improved common household stain resistance - easy to remove.
- ⊙ Improved water, oil and dirt repellence.
- ⊙ UV stable for indoor / outdoor application.
- ⊙ Environmentally friendly.
- ⊙ Tin free.

Application Areas:

Absorbent & dense mineral based interior or exterior substrates i.e. terracotta, fired clay, slate, granite, for floors, table tops, kitchen counter tops, facades, window sills, terraces etc. Also for protection of new and renovation of all kind of mineral substrates sand stone, lime stone or marble.

Typical Properties (Technical Characteristics):

Nature :	Single pack
Colour & Appearance :	Colourless
Clarity :	Clear
Density :	1.000 ± 0.02 gm / cc
Flash point :	45°C

Surface Preparation:

Surface should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence and laitance. If possible wash the surface with clean water. Allow the surface to dry application process for better penetration. Before starting of the application, it is advisable that a test patch should be performed with the customer's approval to ensure that their needs are met. STONEBLAZER FLOOR- WET/GLOSS should be applied as supplied to achieve the desired application effect. It can be applied with a soft, lint-free cloth, sponge, or paint brush.

APPLICATION:

To get a matte effect use one or two coats & remove excess material after each coating from porous & absorbent substrates. To get a glossy surface, remove excess material after first coat & leave excess material after final coat from low Removal of excess material should be removed after, 15 - 20 min of application from porous or a bsorbent substrate and 45 - 50 min of application from low porosity or dense substrate to prevent inconsistencies in the enhancement. The product should be fully cured within 24 - 30 hours. The Substrates which are treated common household stains can be easily removed even after 24 hours.

Cleaning:

Clean the tools by using hydrocarbon solvents like xylene, toluene.

Coverage:

Porous or absorbent substrates - 60 - 70 gms per sq.m
Low porosity substrates - 45 - 55 gms per sq.m.

Precautions:

Do not dilute.
Do not apply on damp & wet substrate.

Packaging:

1 Litre & 5 Litres.

Storage & Shelf Life:

Shelf life is one year from the date of manufacture. Store the material in cool and dry place away from sun heat

WEATHERBLAZER INDIA PVT. LTD.

Plot No. 74, Income Tax Colony, Kotwal Nagar, Pratap Nagar,
Nagpur, Maharashtra 440022