

STONEBLAZER WET LOOK

Exclusives application with enhanced look for all stones.



Product Description:

STONEBLAZER WET LOOK is a stable, VOC compliant, 100% active resins blend that imparts water and stain repellency to substrates while providing an enhanced look.

STONEBLAZER application reduces the capillary absorption of the stone which it has penetrated, but does not clog pores or capillaries. There is therefore little or no impairment of the building material's ability to "breathe".

Application Areas

STONEBLAZER WET LOOK is ideal for water repellence with enhanced look of facades, elevations and slanting roof of sandstone, sand lime, bricks, limestone, marble, granite, brick, jodhpuri and jaipuri stones

Benefits

- ⊙ Provides enhanced (Wet) look to the stone.
- ⊙ Ready to use.
- ⊙ Can be applied by brush, roller or spray.
- ⊙ Very thin liquid - deep penetration.
- ⊙ Maximum reduction of water uptake
- ⊙ Permeability to water vapour: breathability
- ⊙ Resistance to UV light, reduced efflorescence
- ⊙ Extensive penetration, adequate resistance to alkalis
- ⊙ NO ALGAE/FUNGUS:- Along with water it repels dirt/dust particles, results in protection of facades against growth of Algae /Fungus (Micro Organism)
- ⊙ No change in surface appearance
- ⊙ Long lasting effect, outstanding durability & protection
- ⊙ Reduced maintenance: cost saving
- ⊙ Environmental compatibility

Typical Properties (Technical Characteristics)

Nature : Single pack
Appearance & Colour : Very thin liquid, colour colourless to slight pale Yellow colour.
Clarity : Clear
Density : 0.90 ± 0.02 gm / cc
Flash point : 38°C
Penetration depth : 1 - 2 mm

Direction for use:

Surface Preparation: The surface shall be free from oil, grease and dirt. If possible wash the surface with clean water after thorough brushing and Allow the surface to dry for better penetration

Mixing/ Primer Coat: No mixing needed as its ready to use single pack system.

Application Process:

Apply two coats of STONEBLAZER WET LOOK wet on wet by brush, roller or spray in a flooding way i.e. the material shall run down the substrate while application. The maximum the penetration, the best performance it will provide. The performance can be tested only after drying for 24 hours or after 3 days.

If it starts raining, stop treatment and cover the freshly impregnated areas.

Cleaning

Clean the tools by plain water in case of water based and with white spirit, kerosene or xylene solvent in case of solvent based product used.

Coverage

Highly porous surface – 30-35 sq.ft per liter per coat. Poor absorbent surface e.g. marble, granite, - 50-69 sq.ft per liter per coat

Precautions

Do not apply on wet or damp substrate.
Do not dilute.

Packaging-

1 litre, 5 litres & 20 Litres.

Storage & shelf life

Shelf life is one year from the date of manufacture. Store the material in cool and dry place away from sun heat.

WEATHERBLAZER INDIA PVT. LTD.

Plot No. 74, Income Tax Colony, Kotwal Nagar, Pratap Nagar,
Nagpur, Maharashtra 440022